

Eaton 5E UPS

500/650/850/1100/1500/2000VA



5E Range



5E 1100 USB

Ideal for protecting:

- PC, workstation
- NAS, internet access point, TV
- Point of sales, business telephony



Essential line interactive UPS

Line interactive technology at an affordable price

- UPS is securing your data and your equipment by protecting you against power outages and bad power quality
- Work through under & overvoltage without wasting battery thanks to Automatic Voltage Regulation (AVR)
- Unmatched price/performance ratio

Eaton reliability

- Trust a leading manufacturer with decades of experience and high quality standards : CE compliance certified by external agency (TUV)
- Rely on batteries anytime : 5E batteries are permanently recharged (even when off) and UPS can start without mains (Cold-start)
- Avoid back door damages coming through phone lines : 5E USB models are equipped with data line surge protection (Internet/Tel/Fax)
- Ensure piece of mind with 3 years UPS warranty, 2 years battery warranty

Easy integration

- Plug easily any equipment to the UPS (PC, HD TV, internet gateway, etc. thanks to IEC outlets
- Install 5E anywhere thanks to its small size
- Easily manage your UPS from your PC (on USB models):
 - Automatic integration into Windows/MacOS/Linux power management for safe system shutdown
 - Analyze energy use and costs, manage UPS parameters, with Eaton UPS Companion software



Powering Business Worldwide

Eaton 5E UPS

- 1 USB port
- 2 Panel for batteries replacement
- 3 IEC320 10A socket



- 4 6 IEC 10A sockets
- 5 Internet/Tel/Fax protection

Eaton 5E 1100i USB

| TECHNICAL SPECIFICATIONS | 500 | 650 | 650 USB | 850 USB | 1100 USB | 1500 USB | 2000 USB |
|--|--|-----------------------------|--|-------------------|-------------------|-------------------|-------------------|
| Rating (VA/W) | 500 VA / 300 W | 650 VA / 360 W | 650 VA / 360 W | 850 VA / 480 W | 1100 VA / 660 W | 1500 VA / 900 W | 2000 VA / 1200 W |
| Format | Tower | | | | | | |
| Electrical Characteristics | | | | | | | |
| Technology | Line-Interactive | | | | | | |
| Input voltage range without using batteries | 170V - 264V | 170V - 264V | 170V - 280V | 170V - 280V | 170V - 280V | 170V - 280V | 170V - 280V |
| Output voltage | 230V | | | | | | |
| Data line surge protection (Internet/Tel/Fax) | No | No | Yes | Yes | Yes | Yes | Yes |
| Connections | | | | | | | |
| Input | 1 IEC C14 (10A) | | | | | | |
| Outputs | 4 IEC C13 (10A) | IEC models: 4 IEC C13 (10A) | | | 6 IEC C13 (10A) | 6 IEC C13 (10A) | 6 IEC C13 (10A) |
| Batteries | | | | | | | |
| Typical backup times for 1 PC* | 7 min | 16 min | 16 min | 20 min | 45 min | 50 min | 50 min |
| Typical backup times for 2 PC* | - | 6 min | 6 min | 8 min | 20 min | 26 min | 26 min |
| Typical backup times for 3 PC* | - | - | - | - | 7 min | 10 min | 10 min |
| Typical backup times for 4 PC* | - | - | - | - | - | - | 5 min |
| Battery management | Permanent battery recharge, cold start | | | | | | |
| Power Management | | | | | | | |
| Communication ports | No | No | 1 USB port | 1 USB port | 1 USB port | 1 USB port | 1 USB port |
| Eaton UPS Companion software | No | No | Yes (available on www.eaton.com/powerquality/SEA) | | | | |
| Operating conditions, Standards and Approvals | | | | | | | |
| Operating temperature | 0 to 40° | | | | | | |
| Noise level | <40dB | <40dB | <40dB | <40dB | <45dB | <45dB | <45dB |
| Safety | IEC/EN 62040-1 | | | | | | |
| EMC, Performance | IEC/EN 62040-2 | | | | | | |
| Approvals | CE, CB report (TUV) | | | | | | |
| Dimensions D x H x W / Weight | | | | | | | |
| Dimensions | 288 x 148 x 100mm | 288 x 148 x 100mm | 288 x 148 x 100mm | 288 x 148 x 100mm | 330 x 180 x 133mm | 330 x 180 x 133mm | 330 x 180 x 133mm |
| Weight | 3.66kg | 4.6kg | 4.64kg | 5.16kg | 9.22 | 10.46 | 10.46 |
| Customer Service & Support | | | | | | | |
| Warranty | 3 years on electronics, 2 years on battery | | | | | | |

* Backup times are approximate and may vary with equipment, configuration, battery age, temperature, etc.

| Part Numbers | 500 | 650 | 650 USB | 850 USB | 1100 USB | 1500 USB | 2000 USB |
|--------------|--------|--------|-----------|-----------|------------|------------|------------|
| IEC outlets | 5E500i | 5E650i | 5E650iUSB | 5E850iUSB | 5E1100iUSB | 5E1500iUSB | 5E2000iUSB |

In the interests of continuous product improvement, all specifications are subject to change without notice.

SINGAPORE
Tel : +65 6825 1684
Fax : +65 6825 1689
EatonSEA@eaton.com
www.eaton.com/powerquality/SEA

INDONESIA
Tel : +62 21 2949 9000
Fax : +62 21 2949 9001

MALAYSIA
Tel : +603 7804 3618
Fax : +603 7803 6193

THAILAND
Tel : +66 2575 0530
Fax : +66 2575 1579

VIETNAM
Hanoi
Tel : +84 4 3936 5303
Fax : +84 4 3936 5307

Ho Chi Minh
Tel : +84 8 6255 6737
Fax : +84 8 6255 6801

Eaton is the trade name, trademark, and/ or service mark of Eaton Corporation or its subsidiaries and affiliates.